


CDD10-050

1.0 Ton Electric Straddle Stacker

Lifting Height: 2000-3300mm

Load Curve



Advantages Configuration and Performance

- ◉ Separately excited motor, Strong climbing ability.
- ◉ High strength forks.
- ◉ Built-in charger.
- ◉ Automatic lifting limit, Motor and battery life extension.

Safety

- ◉ Stepless speed control system, safe and quiet.
- ◉ Controller with Multiple automatic protection
- ◉ Emergency reversing device/Emergency brake switch.

Built-in charger

Free-maintained battery

Adjustable forks at three choices

24 YEARS TOP1 FORKLIFT MANUFACTURER AND SALER
IN CHINA FOR CONSECUTIVE 24 YEARS

Type	Lift height (mm)	Mast type	Outside width between legs (mm)	Inside width between legs (mm)
CDD10-050	2000/2500/3000/3300	Standard 2-STAGE	1120/1270/1420	970/1120/1270

Feature		
Model		CDD10
Configuration No.		050
Type		Straddle
Mast type		Standard 2-Stage
Load capacity	kg	1000
Load center	mm	600
Wheel base	mm	1204
Operating type		Walkie
Wheels		
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/1/4
Dimension		
Standard lift height	mm	2000/2500/3000/3300
Max.extend height	mm	2387/2887/3387/3687
Mast lowered height	mm	1615/1865/2115/2265
Lowered fork height	mm	55
Fork size(length/width/thickness)	mm	1070/100/40
Overall length	mm	1721
Overall width	mm	940
Outside width between forks	mm	200-812
Inside width between forks	mm	0-612
Min.Turning radius	mm	1411
Min.Aisle width for pallets 800×1200	mm	1970
Min.Aisle width for pallets 1000×1200	mm	2010
MIn.ground clearance	mm	50
Performance		
Travel speed,laden/unladen	km/h	3/3.5
Lift speed,laden/unladen	mm/s	130/230
Lowering speed,laden/unladen	mm/s	130/230
Gradeability,laden/unladen	%	5/7
Electrical configuration		
Drive motor/Lift motor/Steering motor	kW	DC0.63/DC2.0
Battery voltage	V	24
Battery capacity	Ah	70
Brake		Electromagnetic/Regenerative
Controller		HELI(Options CURTIS)
Weight		
Battery weight	kg	48
Service weight with battery	kg	596

* Details of specifications and equipment are based on information available at time of printing and may change without notice.

HIDRALTUR
CARRETILLAS ELEVADORAS

Dirección Comercial: C/Xavier Noguès, 12
Pol. Ind. Can Ribó
08911 Badalona

hidraltura@hidraltura.es www.hidraltura.es